Synology®

Expansion Unit

DX1222



Plug-and-Play Storage Expansion for Synology DiskStation

Synology DX1222 expansion units let you add capacity to your Synology DiskStation¹ on the fly. Instantly leverage up to 12 additional 2.5 or 3.5 inch drives in the same deployment thanks to a small footprint, quick installation, and Synology DiskStation Manager's (DSM) intuitive volume management options. The unit is backed by Synology's 5-year limited warranty.²

Highlights

- Simple Installation
 Add 12 additional drive bays to your DiskStation¹ with minimal disruption
- Fast and Intuitive Setup
 Configure new storage in minutes with Synology DSM's unified tools
- Ready for Synology Drives
 Ensure highest reliability with Synology enterprisegrade drives
- Extended Support

 Backed by Synology's 5-year limited warranty²



Minimal Disruption

Seamlessly expand RAID volumes without reformatting drives with online volume expansion in DSM to minimize service disruptions.



Synology Has You Covered

Keep your business running with the technical support services included in Synology's 5-year limited warranty.²

As Easy As Connecting the Cable

DX1222's **plug-and-play design** and **simple volume management** in DSM make it easy to accommodate surging storage demands in time. A **modest desktop form factor** means you need not sacrifice precious office space.

Achieve More With Synology Drives

Synology enterprise-grade drives, developed in tandem with Synology storage systems, provide proven interoperability and high reliability through rigorous validation. Combine them with Synology DiskStation and DX1222 for a highly reliable and integrated storage setup, and receive long-term Synology updates and support.

Backed by Synology's 5-Year Limited Warranty

Get the most out of your DX1222 with **comprehensive hardware replacement** and **premium technical support**, both included in Synology's 5-year limited warranty.²



Hardware Overview

Front







1	Status Indicator	2	Alert Indicator	3	Power Button	4	Link Indicator
5	Drive Status Indicators	6	Drive Trays	7	Drive Tray Lock	8	Power Port
9	Fans	10	Expansion Port				

Technical Specifications

Hardware

Compatible drive types	12 x 3.5" or 2.5" SATA HDD/SSD (drives not included)
Hot swappable drives	Yes
External port	1 x Expansion port (Mini-SAS HD)
Size (HxWxD)	270 x 300 x 340 mm
Weight	9.02 kg
System fans	2 x (120 x 120 x 25 mm)
AC input power voltage	100 V to 240 V AC
Power frequency	50/60 Hz, single phase
Operating temperature	0°C to 40°C (32°F to 104°F)
Storage temperature	-20°C to 60°C (-5°F to 140°F)
Relative humidity	5% to 95% RH
Maximum operating altitude	5,000 m (16,400 ft)

Environment and Packaging

Environmental safety	RoHS compliant
Package contents	 1 x DX1222 main unit 1 x AC power cord 1 x Accessory pack 1 x Expansion cable 1 x Quick Installation Guide
Optional accessories ³	3.5" SATA HDD: HAT53002.5" SATA SSD: SAT5200
Warranty	5 years ²

Note: Model specifications are subject to change without notice. Please refer to www.synology.com for the latest information.

- 1. Requires DSM 7.0.1-42218 or newer to be installed on the host device.
- 2. The warranty period starts from the date of purchase as stated on your receipt. Visit https://www.synology.com/company/legal/warranty for more information.
- 3. Please refer to our **compatibility list** for the latest optional accessories list.

SYNOLOGY INC.

Copyright © 2021, Synology Inc. All rights reserved. Synology, the Synology logo are trademarks or registered trademarks of Synology Inc. Other product and company names mentioned herein may be trademarks of their respective companies. Synology may make changes to specification and product descriptions at anytime, without notice.

DX1222-2021-ENU-REV002

